## ORDINANCE NO. 409-A

AN ORDINANCE AMENDING AND REPLACING SECTION 2 OF ORDINANCE 409 TITLED "REGULATING SEWER CONNECTIONS TO THE CITY SEWER MAIN IN THE CITY OF SUBLETTE, KANSAS"

BE IT ORDAINED BY THE GOVERNING BODY OF THE CITY OF SUBLETTE, KANSAS:

<u>SECTION 1.</u> The following language shall in its entirety replace Section 2 of Ordinance 409 which was previously passed and approved on the 3<sup>rd</sup> day of February 2014:

"SECTION 2. GENERAL PROVISIONS: Any individual, company, or cooperation doing any type of sewer connection work to a City Sewer Main located on City property or a City easement, regardless if said work is being done on a private line connecting to the same, shall be subject to the following provisions. Sewer connection work to a City Sewer Main shall be defined as work done in which pipes, fixtures, or any other apparatus is connected either directly or indirectly to a city owned line which is used to transport sewer/waste water

- a.) The individual, contractor, or company doing the connection work must abide by the following conditions:
  - 1.) Obtain a permit pursuant to Section 5 of this Ordinance;
  - 2.) Provide and utilize all necessary safety equipment recommended by the Universal Plumbing Code (UPC) and by the Occupational Safety and Health Administration (OSHA) Standards;
  - 3.) Notify Dig Safe and acquire a ticket number and have the area flagged prior to excavation;
  - 4.) Notify the City twenty-four hours (24 hrs.) prior to any backfilling in order for the City to inspect the service line and connection to any city line. Backfilling shall be done as directed by the City Superintendent with fill sand. Any repair or damage sustained due to settling after backfilling shall be the responsibility of individual, contractor, or company doing the work. In the event any city property is damaged, it shall be the responsibility of individual, contractor, or company doing the work to properly remedy such damage as directed by the City Superintendent; this shall include but not be limited to streets, curbs, and guttering.
  - 5.) Provide adequate safety barricades to protect the public;
  - 6.) Cap any abandoned sewer line created by said work and be responsible for the associated cost;
  - 7.) NOT connect any service line directly to a manhole or lift station unless written approval is made by the City; and
  - 8.) Have minimum liability insurance on the work in the amount of one million dollars (\$1,000,000.)"